# \*SHUTTLE HEAT PRESS

## This Ultra-Durable Shuttle Press

- \* Reduces Labor Costs
- \* Increases Productivity Up To 70%



#### **Features:**

- Includes Advanced Touch Screen Technology With Simultaneous Displays And Multiple Presets
- Even Heat & Pressure Distribution
- Dual Quick-Change 16" x 20" (40cm x 50cm) Platens
- Robust Frame
- User-Friendly And Flexible Operations
  - Manual, Semi-Automatic and Fully Automatic Modes
- Automatic Shuttle Between Platens
  - Great For Transfer Applications And Pretreatment Drying
- Optional Foot Pedal Control
- ETL Approved
- Warranty: One Year Parts, 90-day Labor, Ten Years on the Upper Heating Elements



13925 E. 166th Street Cerritos, CA 90703-2431 USA

Tel. 562.404.3000 Fax 562.404.3010

sales@instagraph.com - www.instagraph.com

## **Technical Characteristics**

Platen Size 16" x 20" (40cm x 50cm)

Working pressure From 30 to 110 PSI

Weight 375 Lbs


Max temperature 430°F

Power supply 240 V (single phase + ground)

Electric power 3200 W

Amperage 14 A

## **Accessories**



### **Sponge Plate:**

16" x 20" sponge plate to dry pretreated clothes.



## Set of 4 Quick Change

#### **Platens:**

Useful for precise work.

Dimensions:

3" x 4.8 " - 6" x 6 "

4.8" x 18 " - 10" x 12 "



#### Teflon cover:

Heat resistant Teflon cover to protect the lower plate and make the threading easier.

## **Settings**



New user friendly touch screen with pre-set menus!

Menu with adaptive regulation parameters depending on the job: flex, sublimation on textile, sublimation on rigid substrates, and DTG transfers

#### **Advanced electronics**

- Save up to 5 programs
- Independent time for each plate
- Double timer (main + pre-heat)
- Cycle counters
- Stop cycle function

From 0 to 600 sec (precision +/- 1%). Up to 430°F (precision +/- 1%).

## **Dimensions**

